### HD 5/11 P 240V

Tough, highly portable professional cold-water pressure washer with upright or lie-flat operation.












Order no.

1.520-966.0

- Automatic pressure relief
- For horizontal and vertical operation
- Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

Technical data		
EAN code		4054278147178
Current type	Ph / V / Hz	1 / 240 / 50
Flow Rate	l/h	490
Water feed temperature	°C	max. 60
Operating pressure	bar / MPa	110 / 11
Max. Pressure	bar / MPa	160 / 16
Power rating	kW	2.2
Power cable	m	5
Weight (with accessories)	kg	20.7
Weight incl. packaging	kg	22.8
Dimensions (L × W × H)	mm	351 × 312 × 904

Equipment		
Trigger gun		EASY!Force
High-pressure hose	m	10 / DN 6, 250 bar
Spray lance	mm	840
Pressure switch control		•
Included in delivery.		





### Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

- At last work without getting tired: the EASY!Force high-pressure gun.
- EASY!Lock quick-release locks: durable and robust. And five times faster than screws.



#### First-class mobility

- The integrated carrying handle on the front of the machine enableseasy loading and convenient transport.
- Compact design and low weight.



#### Flexibility

- Vertical and horizontal operation possible.
- Separate parking and transport position for the spray unit.
- The machine offers maximum stability in horizontal operation.





























		Order no.	Description	
TRIGGER GUNS				
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	1
Conversion kit 1 from high pressure hose	2	4.111-050.0	A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance.	[
Conversion kit 2 from device	3	4.111-051.0	Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including adaptors, lance, Easy!Force trigger gun and hose.	[
Conversion kit 3 only EASY!Force	4	4.111-052.0	A conversion kit for the EASY!Force gun, which includes the correct adaptors to conncect to the M22 style lance and hose.	[
SPRAY LANCES				
Rotating spray lances				
Spray lance, 840 mm, rotatable	5	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	ı
LED nozzle light	6	2.680-002.0	LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results.	[
Spray lance, 250 mm, rotatable	7	4.112-027.0	250 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 400 mm, rotatable	8	4.112-024.0	400 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 600 mm, rotatable	9	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1050 mm, rotatable	10	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	11	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	[
Spray lance, 2050 mm, rotatable	12	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	[
Spray lance extender, 1000 mm	13	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	[
Double lance	,			Ť
Double lance, 960 mm	14	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	[

 $<sup>\</sup>blacksquare$  Included in delivery.  $\hfill\Box$  Available accessories.

# **EQUIPMENT FOR HD 5/11 P 240V 1.520-966.0**





















		Order no.	Description	
SPRAY LANCES				Ť
Angular spray lance				
WC and gutter lance	15	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	[
Flexible spray lance				
Flexible lance, 1050 mm	16	4.112-035.0	1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	[
High pressure articulated joint	17	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Gutter cleaner				
Gutter cleaning lance	18	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the specia nozzle the gutter can be cleaned without removing the cover plates.	1 [
Undercarriage spray lance				
Underbody lance	19	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle				
Additional handle for EASY!Lock spray lances	20	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	
PowerControl spray lance		'		
PowerControl spray lance 038	21	4.112-047.0	Infinitely variable pressure adjustment during operation directly in the operator's gripping area, especially for machines without servo control function.	
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 15°				
Power Nozzle 15°, 036	22	2.113-043.0	Flat jet nozzle for stubborn dirt.	•
HP nozzle spray angle 0°				
Power Nozzle 0°, 040	23	2.113-001.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	
Power nozzle spray angle 25°				
Power Nozzle 25°, 036	24	2.113-005.0	Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	. [
Power nozzle spray angle 40°				
Power Nozzle 40°, 040	25	2.113-003.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	[
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, 250 bar, 2 × EASY!Lock	26 27	6.110-034.0 6.110-035.0	10 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $6/155^{\circ}$ C/250 bar.	
High-pressure hose, 10 m, 300 bar, 2 × EASY!Lock	28	6.110-056.0	With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 × 1.5 with anti-kink protection. NW 6/155°C/300 bar	5 [

 $\blacksquare$  Included in delivery.  $\qed$  Available accessories.

















	_			_
		Order no.	Description	
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, 315 bar, 2 × EASY!Lock	29	6.110-031.0	10 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 15 m, 315 bar, 2 × EASY!Lock	30	6.110-030.0	15 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 20 m, 315 bar, 2 × EASY!Lock	31	6.110-032.0	20 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 30 m, 315 bar, 2 × EASY!Lock	32	6.110-014.0	With rotary coupling, 2 × M 22 × 1.5	
High-pressure hose, 15 m, 220 bar, 2 × EASY!Lock	33	6.110-042.0	15 m high-pressure hose M 22 $\times$ 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155 $^{\circ}$ C/220 bar.	
High-pressure hose, 20 m, 220 bar, 2 × EASY!Lock	34	6.110-043.0	with union on both sides, M $22 \times 1.5$ with anti-kink protection. NW $10/155^{\circ}$ C/220 bar	
High-pressure hose, 25 m, 220 bar, 2 × EASY!Lock	35	6.110-044.0		
High-pressure hose, 40 m, 220 bar, 2 × EASY!Lock	36	6.110-045.0		
High-pressure hose, 15 m, 210 bar, 2 × EASY!Lock	37	6.110-059.0	High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. $2x M 22 \times 1.5$ with anti-kink protection.	
High-pressure hose, 40 m, 210 bar, 2 × EASY!Lock	38	6.110-060.0		
High-pressure hose, 10 m, 220 bar, 2 × EASY!Lock	39	6.110-041.0		
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 1,5 m, 400 bar, $2 \times EASY!Lock$	40	6.110-024.0	1.5 m high-pressure hose (DN 8, M $22 \times 1.5$ ) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M $22 \times 1.5$ ).	
High-pressure hose Longlife, 1,5 m, 400 bar, $1 \times \text{EASY!Lock} / 1 \times \text{M22} \times 1.5$	41	6.110-069.0	High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 × 1.5, quick and convenient EASY!Lock hand screw connection.	
High-pressure hose Longlife, 10 m, 400 bar, 2 × EASY!Lock	42	6.110-038.0	Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANTI!Twist. Approved for 400 bar pressure.	

<sup>☐</sup> Available accessories.























		Order no.	Description	
HIGH-PRESSURE HOSES				t
Longlife 400 with unions on both sides				П
High-pressure hose Longlife, 30 m, 400 bar, 2 × EASY!Lock	43	6.110-023.0	With rotary coupling, 2 × M 22 × 1.5	[
High-pressure hose Longlife, 20 m, 400 bar, 2 × EASY!Lock	44	6.110-027.0	with rotary coupling, 2 $\times$ M 22 $\times$ 1.5	ı
High-pressure hose Longlife, 15 m, 400 bar, 2 × EASY!Lock	45	6.110-029.0	With rotary coupling, 2 $\times$ M 22 $\times$ 1.5	
Food industry version with unions on both side	es			Ť
High-pressure hose food grade, 15 m, 250 bar, 2 × EASY!Lock	46	6.110-063.0	15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	[
High-pressure hose food grade, 10 m, 250 bar, 2 × EASY!Lock	47	6.110-051.0	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M $22 \times 1.5$ with anti-kink sleeve.	-
High-pressure hose food grade, 20 m, 250 bar, 2 × EASY!Lock	48	6.110-052.0	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M $22 \times 1.5$ , with kink protection. NW 8/155°C/250 bar.	
Longlife food industry version with unions on	both s	sides		Ť
High-pressure hose food grade Longlife, 10 m, 400 bar, $2 \times EASY!Lock$	49	6.110-053.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, $2 \times M$ $22 \times 1.5$	
High-pressure hose food grade Longlife, 20 m, 400 bar, 2 × EASY!Lock	50	6.110-054.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	
Special hoses				Ī
High-pressure hose curved, 1.5 m, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5	51	6.110-068.0		
STROMGENERATOR				Ī
PGG 6/1	52	1.042-208.0		
ROTARY NOZZLES (DIRT BLASTERS)				ľ
Dirt Blaster, small				Ī
Dirt Blaster Nozzle, small, 040	53	4.114-020.0	With rotating point jet for more efficient removal: the new performance dirt blaster with nozzle size 040 achieves up to 50% higher cleaning and area performance than its predecessor.	
Dirt blaster, large				
Dirt Blaster Nozzle, large, 040	54	4.114-041.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzland bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	е
MULTIPLE-JET NOZZLES				
Triple nozzles				ĺ
Triple Nozzle, 036	55	4.117-031.0	Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application.	
NOZZLE UNION / SPACER				
Nozzle union				ĺ
Nozzle screws	56	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	

 $<sup>\</sup>hfill \square$  Available accessories.























				$\top$
	<u> </u>	Order no.	Description	_
PIPE CLEANING				
Pipe cleaning hose, ID 6	1			١,
Hose assembly TR pipe cleaning DN6 14MPa	57	6.110-048.0	10 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	_
Pipe cleaning hose	58	6.110-049.0	20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	_
Pipe cleaning hose, DN 6, 30 m	59	6.110-050.0	30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning nozzle				
Dirt blaster pipe cleaning D21/040	60	4.765-001.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	[
Dirt blaster pipe cleaning D30/040	61	4.765-004.0	jets ensure the necessary forward movement, as well as convenient handling.	[
Pipe cleaning nozzle	62	5.763-015.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for	[
	63	5.763-020.0	environmentally-friendly cleaning of blocked drains and pipes.	[
	64	5.763-017.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	[
Rotating pipe cleaning nozzle	65	6.415-428.0	Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	
FLOOR AND HARD SURFACE CLEANER				
Hard surface cleaner FR Classic				
FR Classic surface cleaner	66	2.111-016.0	The ideal entry-level model in the Kärcher surface cleaner range for cleaning surfaces indoors and outdoors. With splash guard and up to 150 bar working pressure.	1
Hard surface cleaner FR 30	•			
FR 30 Surface Cleaner	67	2.111-011.0	Up to 10 times greater area coverage compared with the conventional high pressure jet.	[
Hard surface cleaner FR 30 ME				
FR 30 ME surface cleaner	68	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Machine-specific nozzle kit for FR				Ť
Nozzle kit for FR, 450 l/h - 500 l/h	69	2.640-482.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h).	
Machine-specific nozzle kits for FR Classic				Ť
Nozzle kit for FR Classic, 040	70	2.885-312.0	Nozzle kit specifically for FR Classic surface cleaner.	
Available accessories			<u> </u>	_

 $<sup>\</sup>hfill \square$  Available accessories.



























		Order no.	Description	
FOAM SYSTEMS		Graci no.	- State Patrick	+
Cup foam lance				
Cup foam lance Basic 1, 350 l/h - 600 l/h	71	4.112-053.0	For high-pressure cleaners with a flow rate of 350-600 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	
1-litre cleaning agent container for cup foam lance basic	72	5.071-414.0		
1-litre cleaning agent container for cup foam lance advanced	73	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Cup foam lance Advanced 1, 400 l/h - 600 l/h	74	4.112-063.0		Е
Cup foam lance DUO Advanced 1, 400 l/h - 600 l/h	75	4.112-067.0		
Inno Foam Set				
Inno foam kit with detergent injector	76	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set				
Easy Foam Set with RM injector	77	2.112-010.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set				
Nozzle kit 055 z. Inno/Easy Set 500 - 600 l/h	78	2.111-009.0	Optimal adaptation to different machine outputs for economic use.	
Foam nozzle mounting kit				
Foam nozzle kit	79	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
MIXERS AND INJECTORS				
HP detergent injector				
Detergent injector for high and low pressure (without nozzles)	80	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressure	81	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	
Machine-specific nozzle kit with order no. 3.63	7-170			
Nozzle insert trapezoidal thread HD-GER.	82	4.769-005.0	For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 3.637-001				
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	83	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to 1100 l/h	84	4.769-001.0	For low pressure with machines up to 1.100 l/h	





























		Order no.	Description	L
QUICK CONNECT				Ļ
Quick-fitting pipe union coupler trapezo	85	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	
Quick-fitting pipe union plug nipple tra	86	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M $22 \times 1.5$ external thread.	
DRUM AND TANK CLEANING				
Add-on kit mud sucker	87	2.641-798.0		
OTHER HP ACCESSORIES		'		
Starting current limiter	88	2.637-495.0	Reduces starting current in single-phase supply and protects line fuse.	
Jet gun	89	2.869-067.0	Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	
COUPLING PARTS				
Rotary coupling				
Rotary coupling	90	4.111-021.0	Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector Easy!Lock. With grip protection.	
Connector	'			
Nozzle connector/screw connector	91	4.111-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1 \times M$ 22 $\times$ 1.5 and $1 \times M$ 18 $\times$ 1.5.	
Y distributor	92	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	Е
Short spray unit	93	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	t C
Adapter EASY!Lock				
Adapter 1 M22AG-TR22AG	94	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	95	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	Е
Adapter 3 M22IG-TR22AG	96	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	Г
Adapter M22 - Swivel	97	4.111-032.0	M22 $\times$ 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	1
Adapter 5 TR22IG-M22AG	98	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	

<sup>☐</sup> Available accessories.

























		Order no.	Description	
COUPLING PARTS		<u> </u>		<del>                                     </del>
Adapter EASY!Lock				
Adapter 6 TR22IG-M22AG	99	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	100	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	101	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
Coupler -2xM22x1,5	102	4.111-037.0	Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \text{ M } 22 \times 1.5 \text{ m}$ .	
ADAPTER for replacement TR22IG-M22AG Er	103	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
HOSE REELS				
Automatic, self-winding hose reels				
Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\text{m}}$	104	2.639-257.0		
Automatic hose reel, powder-coated steel / plastic, 20 m	105	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / synthetic material hose drum, 20 m	106	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated, 20 m	107	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	. 🗆
Hose reel, automatic, basalt grey-coated, 20 m	108	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	109	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	110	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Powder-coated swivel holder	111	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Stainless steel swivel holder	112	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	

 $<sup>\</sup>hfill\square$  Available accessories.























		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Drive for roller brush 500	113	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard for roller brush 500	114	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	
Roller brush 500 soft	115	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	
Roller brush 500 medium	116	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	
Roller brush 500 hard	117	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
Brush hard	118	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	
Brush medium	119	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	
Brush soft	120	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
Telescopic				
TL low pressure adapter	121	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
Telescopic lance TL 7 F	122	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	
Telescopic lance TL 7 H	123	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach.	. 🗆
Telescopic lance TL 10 H	124	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
Telescopic lance TL 10 C	125	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	
Telescopic lance TL 14 C	126	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	

<sup>☐</sup> Available accessories.





















		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING	<u> </u>			t
Telescopic				
TL high pressure adapter	127	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)				
Wet blasting attachment with flow control (without nozzles)	128	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	[
Wet blasting attachment without flow control (nozzles not included)	129	4.115-006.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	[
Nozzle pack for wet blasting attachment				
Nozzle pack TR wet jet set 0035	130	2.112-021.0	Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0   4.115-006.0.	
Boron carbide nozzle		'		
Boron carbide nozzle, for machines as of 1000 I/h	131	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	[
WATER CONNECTION				
Geka coupling				
With hose nozzle, R 1/2"	132	6.388-461.0	with hose liner	[
With hose nozzle, R 3/4"	133	6.388-455.0		[
With hose nozzle, R 1"	134	6.388-465.0	with hose barb	[
With female thread, R 3/4"	135	6.388-473.0	with female thread	[
Suction filter	•			
Water filter	136	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	
Suction filter with check valve	137	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	[
Fine-mesh water filter				
Add-on kit water filter universal	138	2.637-020.0		[
Fine-mesh water filter with adapter	139	4.730-102.0	Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	,
Water supply hose				Ī
Water supply hose	140	4.440-038.0	NW 13 R1" / R 3/4", up to 30 °C	

 $<sup>\</sup>hfill\square$  Available accessories.













		Order no.	Description	
WATER CONNECTION		<u>'</u>		
Water supply hose				
Water supply hose	141	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
Backflow check valve	•			
Backflow preventer	142	2.641-374.0	To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. – hot water resistant up to 80 °C – tested according to IEC 60335-2-79 – integrated leakage protection	
WASHING BRUSHES				
Push-on washing brush				
Push-on wash brush, M 18 × 1.5	143	4.113-001.0	Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 × 1.6.	
Rotating washing brush				
Rotating wash brush for < 800 l/h machines, nylon bristles	144	4.113-004.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to $60^{\circ}$ C. (M $18 \times 1.5$ , replaceable brush insert).	
Rotating wash brush for < 800 l/h machines, natural bristles	145	4.113-003.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to $60^{\circ}$ C, M $18 \times 1.5$ (replaceable brush insert).	

<sup>☐</sup> Available accessories.